



Termination Bar

Firestone Item Number: W56RAC3061

DESCRIPTION:

Termination Bar is intended for attaching and sealing flashing terminations as outlined by Firestone Specifications and Details.

METHOD OF APPLICATION:

1. Substrates must be free from dust, dirt, oil, water and other contaminants. Wall areas above Termination Bar must be waterproof. Install per Firestone Specifications and Details.
2. Install Firestone Water Block Seal behind top of flashing.
3. Anchor bar through pre-punched holes at a rate to maintain a seal (max. 12" o.c. (304.8 mm)).
4. Install flat side of bar towards flashing so a "lip" forms a reservoir for Firestone Lap Sealant.
5. Keep each 10' (3.1 m) length of Termination Bar separated from adjoining bar by 1/4" (6.3 mm).
6. Install termination bar vertically where base flashing(s) end.
7. Remove excess flashing material above bottom of lap sealant reservoir channel.
8. Install Firestone Lap Sealant into reservoir channel.

STORAGE:

Store in unopened original containers protected from the weather.

PACKAGING:

50 - 10 ft (3.1 m) sections per tube
86 lbs (39 kg) per tube

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Material:	3003-H14, 3105-H14 or 6063-T5, or T6 Aluminum
Length:	10 ft (3.1 m)
Height:	1.08" (27.4 mm)
Thickness:	0.087" (2.7 mm)
Holes:	Slotted, 0.28" x 0.39" (7.1 x 9.9 mm) 30 at 3.9" (99.8 mm) o.c.

PRECAUTIONARY DATA:

- Do not use as a batten strip.
- Where field cutting is necessary, remove any burrs from bar.
- Clean up shavings, etc. that may occur from field cutting.
- Termination bars must be installed directly to the wall surface, not to existing sheet metal, flashings, etc.
- Install termination bar on hard, smooth surfaces only. Do not install on substrates where seal is lost at mortar joints, etc.
- Do not install termination bar to wood or other porous surfaces.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 67%
Manufacturing Locations: Cleveland, OH

Firestone Building Products Company

250 W. 96th Street, Indianapolis, IN 46260
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpc.com