



QuickSeam™ Splice Tape

Firestone Item Numbers:

- 3" x 100': W56RAC1603
- 4" x 100': W56RAC160A
- 6" x 100': W56RAC1626
- 7" x 100': W56RAC1617

DESCRIPTION:

Firestone 3" (76.2 mm), 4" (101.6 mm) 6" (152.4 mm) and 7" (177.8 mm) QuickSeam Splice Tape is designed for field splicing of RubberGard™ EPDM membrane panels and flashing.

METHOD OF APPLICATION:

1. Use QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to Firestone Specifications and Details.
3. Refer to application instructions for specifics: Technical Database, www.firestonebpco.com.

PHYSICAL PROPERTIES:

| Property | Minimum Performance |
|--------------|--------------------------------------|
| Base: | Rubber Polymers |
| Color: | Black |
| Solvents: | None |
| Solids: | 100% |
| Cured State: | Cured |
| Thickness: | 0.030" (0.77 mm) ± 0.005" (0.127 mm) |

PACKAGING:

- 3" (76.3 mm) x 100' (30.48 m) roll, 6 rolls per carton
- 4" (101.6 mm) x 100' (30.48 m) roll, 4 rolls per carton
- 6" (152.4 mm) x 100' (30.48 m) roll, 2 rolls per carton
- 7" (177.8 mm) x 100' (30.48 m) roll, 2 rolls per carton
- 40 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



SHELF LIFE:

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

STORAGE:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

PRECAUTIONARY INFORMATION:

Refer to Material Safety Data Sheet (MSDS).

LEED INFORMATION:

| | |
|-----------------------------------|--------------|
| Post Consumer Recycled Content: | 0% |
| Post Industrial Recycled Content: | 0% |
| Manufacturing Location: | Prescott, AR |

PATENTS:

The products contained herein, or the methods of their use, may be covered by one or more of the following United States Patents: 5,242,727; 5,520,761; 5,976,292.



Firestone Building Products Company
250 W. 96th Street, Indianapolis, IN 46260
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com