

# TECHNICAL SPECIFICATIONS

## T390F FILTER TANKS | FILTER TANKS

With the ability to flow up to 700 GPM through two large filters, the Filtrific<sup>®</sup> T390F is the perfect solution for large, high-flowing water features. Innovative design elements such as a standard 6" intake port, which can be cut off to create a 10" intake port, allow for unlimited creativity when designing and building anything from landscape water features to architectural pools.



#### **T390F FILTER TANK**

#### MODEL: T390F

#### FEATURES:

- Weight: 256 lbs
- Dimensions: L: 70", W: 51.5", H: 48"
- 6" / 10" combination intake port handles flow rates up to 700 GPM (42,000 GPH)
- Handles flow rates up to 1,340 GPM (80,400 GPH) when used with RHI5 series Filter Skimmers pg 32
- 390 gallon Filter Tank (provides 270 gallons of waterin motion reserve @ 9" residual water depth)
- Can be placed away from the water feature

- Accepts interchangeable skimmers
- Large pumping chamber
- Bolt down integrated lid system
- Convenient filter access (Filter Baskets purchased separately)
- Removable Filter Carriage
- Front & back discharge ports for up to four pumps
- Front and back additional capacity ports for expandable water containment



## TECHNICAL SPECIFICATIONS

### T390F FILTER TANK | FILTER TANKS

### TECHNICAL SPECIFICATION

MODEL: T390F FILTER TANK (filtered pump vault for submersible pumps & pumping accessories)

The Filter Tank shall be able to handle an intake water flow of 700 gallons per minute through a 10" intake port.

The Filter Tank shall be able to accept two removable filter baskets with a detachable 316 stainless steel element for periodic system cleaning. The Filter Tank shall feature a removable, integrated filter carriage, providing unobstructed access to the pump chamber. The Filter Tank shall include 11 internal pipe connection ports. The Filter Tank shall include a bolted lid with an inner filter element access cap for convenient filter removal.

The Filter Tank's dimensions shall be 70" x 51.5" x 48".

The Filter Tank shall be manufactured by Filtrific Company LLC, Woodinville Washington.





Filtrific<sup>®</sup> 15500 Woodinville-Redmond Road Suite C-100 Woodinville, WA 98072 P: 800.906.0604 • F: 425.482.9559

#### www.filtrific.com